

PHILIPS

RESPIRONICS

BiPAP A40

Tailored ventilation

Because every patient is different

Because our innovations are inspired by you and your patients, the bi-level ventilator BiPAP A40 has been designed to combine ease-of-use and comfort with technological innovations that adapt to your patient's condition to deliver enhanced therapy.

Based on a familiar platform, BiPAP A40 comes with well-known and clinically proven Philips Respiration technology such as Auto-Trak, AVAPS and a Dry Box humidifier design. The device is capable of non-invasive and invasive pressure ventilation, up to 40 cmH₂O, providing treatment for your chronic insufficiency respiratory patients.

BiPAP A40 can provide autonomy and increased support to patients, thanks to its specifically designed battery module.

The device features AVAPS-AE, an innovative mode of ventilation designed to help clinicians during the titration process, while maintaining comfort and therapy optimization. This new ventilation mode helps in providing long-term therapy compliance regardless of changes to the body position, sleep stages and respiratory mechanics.



OXYCARE
Medical Group GmbH
FON +49(0)421 48 99 66 • www.oxygene.eu

MEMBER
OF



AVAPS-AE mode

In AVAPS-AE mode, the device monitors the patient's upper airway resistance and automatically adjusts the delivered EPAP required to maintain an airway. Simultaneously, BiPAP A40 automatically adjusts pressure support to maintain a target tidal volume, and when the breath rate is set to Auto, the device will adjust the back-up breath rate based on the patient's spontaneous respiratory rate.

Ordering information

Part no.

Devices

BiPAP A40, International*	111169
BiPAP A40, Australia*	111171
BiPAP A40, Canada*	111173
BiPAP A40 Canada, Heated Tube core pkg	111174

* contains BiPAP A40 ventilator with SD card, power cord, AC power adapter, user manual, ultrafine filter, grey foam filter, tubing, and carrying case

Accessories

A-Series humidifier, International	1111552
A-Series, heated tube humidifier, International	1111555
Battery module	1096770
Detachable battery	1043570
Ultrafine filter kit	1063096
Foam filter kit	1063091
Power supply	1081167
Power cord, Europe	1039014
Power cord, UK	1039026
Power Cord, Canada	1038928
Performance tubing 22 mm	1032907
Performance tubing 15 mm	1074400
EncorePro 2 software	1054785
DirectView software	1005297

Product specifications

Ventilation modes	• CPAP • S • S/T • PC • T • AVAPS-AE
Hybrid ventilation	• AVAPS (Average Volume Assured Pressure Support) • AVAPS-AE
IPAP	4 – 40 cmH ₂ O
EPAP	4 – 25 cmH ₂ O
Target tidal volume (AVAPS and AVAPS-AE)	200 – 1500 ml
Breath rate	0 – 40 bpm (4 – 40 bpm in T mode)
Inspiratory time	0.5 – 3 sec
Triggering and cycling	• Auto-Trak • Sensitive Auto-Trak • Flow triggering
Rise time	1 (100 ms) – 6 (600 ms)
Size	21.6 cm W x 19 cm L x 11.5 cm H
Weight	1.9 kgs (with power supply)
Noise level	< 28 dBA at 10cmH ₂ O
Humidification	• System One humidity control and 'Dry Box' technology • Heated tube humidification
Alarms	• Patient disconnection • Apnea • Low minute ventilation • Low tidal volume (with AVAPS/AVAPS-AE only) • High respiratory rate
Monitoring	• Pressure • Tidal volume • Minute ventilation • Respiratory rate • Leak • I/E ratio
Battery backup	Detachable battery module: 9h 45 min at IPAP 12 cmH ₂ O/EPAP 7 cmH ₂ O and 12 bpm (restrictive profile)
DC power source	• 12 VDC, 5.0 A (external battery) • 24 VDC, 4.2 A (power supply)
Data management	• Encore and DirectView software • Compatible with oximetry module • Advanced detection of residual respiratory events apnea/hypopnea index, obstructed airway apnea, hypopnea, periodic breathing, RERA, large leak and snore)
Remote control	Compatible with Omnilab Direct
Polygraph and polysomnograph connections	• Direct connection to Alice PDx and Alice6 PSGs • Omnilab Connect to connect to most PSG systems

BiPAP A40, Auto-Trak, AVAPS, AVAPS-AE, EncorePro, DirectView, and Alice are trademarks of Koninklijke Philips N.V. All rights are reserved.

© 2016 Koninklijke Philips N.V. All rights reserved. Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. or their respective owners.

MCI 4107448 PN461981



Philips Respironics
1010 Murry Ridge Lane
Murrysville, PA 15668 USA

www.philips.com/respironics